

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (cancelled)

2. (currently amended) ~~The base station apparatus according to claim 1~~ A base station apparatus for communicating with a specific base station and at least one terminal that is movable relative to the specific base station, wherein

the base station apparatus is movable relative to the specific base station, and when the at least one terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the at least one terminal, and

the base station apparatus communicates with the specific base station and the terminal respectively according to an ATM (asynchronous transfer mode) communication system in which user data and control information are allocated to at least one ATM cell without distinction between the user data and the control information.

3. (original) The base station apparatus according to claim 2, wherein

the user data is data that is transmitted through a traffic channel, and

the control information is information that is transmitted through a control channel.

4. (original) The base station apparatus according to claim 2, wherein, when the base station apparatus communicates with the specific base station and the terminal, respectively, unique VPI (virtual path identifier) and VCI (virtual channel identifier) are allocated to the at least one ATM cell that includes the control information, the VPI and VCI indicating that the at least one ATM cell includes the control information.

5. (original) The base station apparatus according to claim 2, comprising:

a specific base station interface section for performing radio communication with the specific base station, wherein the specific base station interface section produces a used-channel reception status signal that indicates a reception status of a channel that is being used between the specific base station and the base station apparatus and an unused-channel reception status signal that indicates a reception status of a second channel different from the channel that is being used; and

a base station control section determines whether a hand-over is to be carried out or not, based on the used-channel reception status signal and the unused-channel reception status

signal which are input from the specific base station interface section, wherein, when it is determined that the hand-over is to be carried out, the base station control section selects a service area to which the hand-over is to be carried out.

6. (original) The base station apparatus according to claim 5, further comprising:

- a terminal interface section;
- a VPI conversion section; and
- a VPI database section for storing VPI data,

wherein

the specific base station interface section extracts an ATM cell as a first ATM cell from a reception frame received from the specific base station, outputs the first ATM cell to the VPI conversion section, maps an ATM cell input from the VPI conversion section into a transmission frame as a second ATM cell, and transmits the transmission frame to the specific base station,

the terminal interface section communicates with the terminal, extracts an ATM cell as a third ATM cell from a reception frame received from the terminal, outputs the third ATM cell to the VPI conversion section, maps an ATM cell input from the VPI conversion section into a transmission frame as a fourth ATM cell, and transmits the transmission frame to the terminal,

the VPI conversion section refers to the VPI data stored in the VPI database, converts the VPI data of the input first ATM cell and outputs a result to the terminal interface section, converts the VPI data of the input third ATM cell and outputs a result to the fixed base station interface section, and

the mobile base station control section outputs the converted VPI data to the VPI database.

7. (currently amended) ~~The base station apparatus according to claim 1~~ A base station apparatus for communicating with a specific base station and at least one terminal that is movable relative to the specific base station,

wherein, the base station apparatus is movable relative to the specific base station, and when the at least one terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the at least one terminal, and

when the terminal moves from a first service area to a second service area of the specific base station, the base station apparatus carries out hand-over processing of the terminal on behalf of the terminal.

8. (currently amended) ~~The base station apparatus according to claim 1~~ A base station apparatus for communicating

with a specific base station and at least one terminal that is movable relative to the specific base station, wherein

the base station apparatus is movable relative to the specific base station, and when the at least one terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the at least one terminal, and

the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

9. (original) The base station apparatus according to claim 7, wherein, when a plurality of terminals move from the first service area to the second service area, the base station apparatus carries out hand-over processing of the plurality of terminals as one unit.

10. (currently amended) The base station apparatus according to claim [[1]] 2, wherein the base station apparatus is installed in transporting means for transporting a user of a terminal.

11. (currently amended) The base station apparatus according to claim [[1]] 2, wherein the specific base station is fixedly provided on the ground.

12. (cancelled)

13. (currently amended) ~~The communication system according to claim 12~~ A communication system comprising:

a specific base station;

a terminal that is movable relative to the specific base station; and

a base station apparatus for communicating with the specific base station and the terminal, wherein

the base station apparatus is movable relative to the specific base station, and when the terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the terminal,

wherein the base station apparatus communicates with the specific base station and the terminal respectively according to an ATM (asynchronous transfer mode) communication system in which user data and control information are allocated to ATM cells without distinction between the user data and the control information.

14. (original) The communication system according to claim 13, wherein, when the base station apparatus communicates with the specific base station and the terminal, respectively, unique VPI and VCI are allocated to the ATM cells that include the control information, the VPI and VCI indicating that the ATM cells include the control information.

15. (original) The communication system according to claim 13, wherein the base station apparatus comprises:

a specific base station interface section; and

a base station control section,

wherein the specific base station interface section carries out a radio communication with the specific base station, generates a used-channel reception status signal that indicates a reception status of a channel that is being used between the specific base station and the base station apparatus and an unused-channel reception status signal that indicates a reception status of a second channel different from the channel that is being used, and outputs these signals to the base station control section, and

the base station control section determines whether a hand-over is to be carried out or not, based on the used-channel reception status signal and the unused-channel reception status signal, and selects a service area to which the hand-over is to

be carried out when it is determined that the hand-over is to be carried out.

16. (original) The communication system according to claim 15, wherein the base station apparatus further comprises:

a terminal interface section;

a VPI conversion section; and

a VPI database section for storing VPI data,

wherein the specific base station interface section extracts ATM cells from a reception frame received from the specific base station as first ATM cells, outputs the first ATM cells to the VPI conversion section, maps ATM cells input from the VPI conversion section into a transmission frame as second ATM cells, and transmits the transmission frame to the specific base station,

the terminal interface section communicates with the terminal, extracts ATM cells from a reception frame received from the terminal as third ATM cells, outputs the third ATM cells to the VPI conversion section, maps ATM cells input from the VPI conversion section into a transmission frame as fourth ATM cells, and transmits the transmission frame to the terminal,

the VPI conversion section refers to the VPI data stored in the VPI database section, converts the VPI data of the input first ATM cells and outputs a result to the terminal interface section, converts the VPI data of the input third ATM



cells and outputs a result to the fixed base station interface section, and

the mobile base station control section outputs the converted VPI data to the VPI database section.

17. (currently amended) ~~The communication system according to claim 12~~ A communication system comprising:

a specific base station;

a terminal that is movable relative to the specific base station; and

a base station apparatus for communicating with the specific base station and the terminal, wherein

the base station apparatus is movable relative to the specific base station, and when the terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the terminal,

wherein, when the terminal moves from a first service area to a second service area of the specific base station, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

18. (currently amended) ~~The communication system according to claim 12~~ A communication system comprising:

a specific base station;

a terminal that is movable relative to the specific base station; and

a base station apparatus for communicating with the specific base station and the terminal, wherein

the base station apparatus is movable relative to the specific base station, and when the terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the terminal,

wherein the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

19. (currently amended) ~~The communication system according to claim 12~~ A communication system comprising:

a specific base station;

a terminal that is movable relative to the specific base station; and

a base station apparatus for communicating with the specific base station and the terminal, wherein

the base station apparatus is movable relative to the specific base station, and when the terminal has moved relative to the specific base station, the base station apparatus moves relative to the specific base station substantially in the same direction as a move direction of the terminal,

wherein, when a plurality of terminals move from the first service area to the second service area, the base station apparatus collectively carries out a hand-over processing of the plurality of terminals as one unit.

20. (currently amended) The communication system according to claim [[12]] 13, wherein the base station apparatus is installed in transporting means that transports a user of the terminal.

21. (currently amended) The communication system according to claim [[12]] 13, wherein the specific base station is fixedly provided on the ground or is fixed relative to the ground surface.

22. (original) A communication method comprising the steps of:

(a) providing first and second service areas by a first base station;

(b) providing a second base station having a third service area;

(c) providing the second base station so that the third service area is superimposed on the first service area;

(d) when a plurality of terminals move from the first service area to the second service area, moving the second base station so that the third service area covers the moved plurality of terminals;

at the second base station,

(e) collectively generating first data required for a hand-over processing associated with movement of the plurality of terminals from the first service area to the second service area, on behalf of the plurality of terminals, to output the generated first data to the first base station; and

at the first base station,

(f) collectively generating for the plurality of terminals second data necessary for the hand-over processing of the plurality of terminals in response to the input first data to output the generated second data to the second base station.

23. (original) The communication method according to claim 22, wherein

at step (e), the second base station outputs the generated first data in ATM (asynchronous transfer mode), and

at step (f), the first base station outputs the generated second data to the second base station in the ATM.

24. (original) The communication method according to claim 22, wherein the hand-over processing is carried out only between the first terminal and the second terminal on behalf of the plurality of terminals.

25. (original) The base station apparatus according to claim 2, wherein, when the terminal moves from a first service area to a second service area of the specific base station, the base station apparatus carries out hand-over processing of the terminal on behalf of the terminal.

26. (original) The base station apparatus according to claim 2, wherein the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

27. (original) The base station apparatus according to claim 7, wherein the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific

base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

28. (original) The base station apparatus according to claim 8, wherein, when a plurality of terminals move from the first service area to the second service area, the base station apparatus carries out hand-over processing of the plurality of terminals as one unit.

29. (currently amended) The base station apparatus according to claim ~~[[1]]~~ 2, wherein the specific base station is fixed relative to the ground surface.

30. (original) The communication system according to claim 13, wherein, when the terminal moves from a first service area to a second service area of the specific base station, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

31. (original) The communication system according to claim 13, wherein the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

32. (original) The communication system according to claim 17, wherein the base station apparatus communicates with a plurality of specific base stations and, when the terminal moves from a first service area of a first specific base station among the plurality of specific base stations to a second service area of a second specific base station among the plurality of specific base stations, the base station apparatus carries out a hand-over processing of the terminal on behalf of the terminal.

33. (original) The communication system according to claim 13, wherein, when a plurality of terminals move from the first service area to the second service area, the base station apparatus collectively carries out a hand-over processing of the plurality of terminals as one unit.

34. (currently amended) The communication system according to claim ~~[[12]]~~ 13, wherein the specific base station is fixed relative to the ground surface.